

## Data Sheet

### Diode Driver D 3300-60-W

#### Features

Driver for laser diodes  
 High accuracy  
 High current stability  
 Very low ripple current  
 Excellent dynamic performance  
 No overshoot, no ringing  
 High output impedance




#### Specification Diode Unit

Diode current	2A.....60A
Diode voltage	0V.....55V
Supply voltage	28V...60V
Output power	3300W max.
Accuracy	± 1%
Temperature stability	50ppm / °C
Current ripple	<1%
Settling time	<1ms
Rise time	<300µs
Diode current monitor	0V...5V±0A...60A
Diode voltage monitor	0V...5V±0V...55V
Auxiliary voltage outputs	+5.1V (max. 200mA), +15V, -15V (max. 200mA each)
Reference voltage output	+5V (max. 2mA)

#### Signal Inputs / Outputs

Diode current set point 1	0V...5V	60A
Diode current set point 2	0V...5V	
Shut Down	Open Collector / TTL	
Diode current monitor	0V...5V	
Ready	Open Collector	



#### General Specifications

Temperature range	0...+45°C
Cooling system	Water
Dimensions	218 x 88 x 68mm
Weight	1,4 kg
Ordering Code	10100226

#### Description

The D 3300-60-W is a high-precision water-cooled laser diode driver.

This technology has a lot of advantages and is particularly suited for driving laser diodes. It offers high accuracy and current stability, excellent dynamic performance, high output impedance and low electromagnetic interference.

No current overshoot or ringing arise when altering output current or when load impedance changes abruptly.

Two operating modes are available, mode Laser On/Off and mode Auto On.

The device is well suited to build up laser systems, which are controlled manually, by microcontroller system or PLC system.



#### Warning!

**Risk of exposure of hazardous laser radiation  
 in combination with laser light emitting devices!**

Technical subjects to change without notice.